

GOODWE

ET G2 Series

6-15kW | Three Phase | Up to 3 MPPTs
Hybrid Inverter (HV)

The ET G2 Series is the latest iteration of the ET Series and has been specially designed to accommodate households' increasing demand for electricity consumption while delivering additional benefits that cater to flexible residential needs.

This inverter features an elegant and sleek design that can harmonize beautifully with the house's aesthetic. With the addition of 12kW and 15kW higher power capacities, the ET G2 is now equipped to deliver even more powerful generation, allowing for optimal energy harvesting. It supports parallel connections with up to 6 units, ideal for expanding energy needs. Additionally, smart load control, 100% unbalanced output, and a focus on system reliability and safety enable versatile and sustainable applications.



Smart Control & Monitoring

- Integrated dry contact for external loads
- Backup with UPS-level switching <10ms
- Peak shaving



Friendly & Thoughtful Design

- Plug & Play installations
- Elegant and compact design



Superb Safety & Reliability

- AFCI optional¹
- IP66 ingress protection
- Type II SPD on DC & AC sides



Flexible & Adaptable Applications

- Maximum 16A DC input current per string
- Up to 160% PV input oversizing
- Parallel connection capability for increased output power

¹: Optional functions or devices are purchased separately.

Technical Data		GW6000-ET-20	GW8000-ET-20	GW10K-ET-20	GW12K-ET-20	GW15K-ET-20
Battery Input Data						
Battery Type				Li-Ion		
Nominal Battery Voltage (V)				500		
Battery Voltage Range (V)				150 ~ 720		
Start-up Voltage (V)				150		
Number of Battery Input				1		
Max. Continuous Charging Current (A)	30	30	40	40	40	40
Max. Continuous Discharging Current (A)	30	30	40	40	40	40
Max. Charging Power (W)	9000	12000	15000	18000	24000	
Max. Discharging Power (W)	6600	8800	11000	13200	16500	
PV String Input Data						
Max. Input Power (W) ¹	9600	12800	16000	19200	24000	
Max. Input Voltage (V) ²				1000		
MPPT Operating Voltage Range (V)				120 ~ 850		
Start-up Voltage (V)				150		
Nominal Input Voltage (V)				620		
Max. Input Current per MPPT (A)				16		
Max. Short Circuit Current per MPPT (A)				24		
Number of MPP Trackers	2	2	3	3	3	
Number of Strings per MPPT				1		
AC Output Data (On-grid)						
Nominal Output Power (W)	6000	8000	10000	12000	15000	
Nominal Apparent Power Output to Utility Grid (VA)	6000	8000	10000	12000	15000	
Max. Apparent Power Output to Utility Grid (VA) ³	6000	8000	10000	12000	15000	
Max. Apparent Power from Utility Grid (VA)	12000	16000	20000	20000	20000	
Nominal Output Voltage (V)				400 / 380, 3L / N / PE		
Output Voltage Range (V) ⁴				170 ~ 290		
Nominal AC Grid Frequency (Hz)				50 / 60		
AC Grid Frequency Range (Hz)				45 ~ 65		
Max. AC Current Output to Utility Grid (A) ⁵	8.7	11.6	14.5	17.4	21.7	
Max. AC Current From Utility Grid (A)	15.7	21.0	26.1	26.1	26.1	
Power Factor				0.8 leading ~ 0.8 lagging		
Max. Total Harmonic Distortion				<3%		
AC Output Data (Back-up)						
Back-up Nominal Apparent Power (VA)	6000	8000	10000	12000	15000	
Max. Output Apparent Power without Grid (VA)	6000 (12000 @60sec) ⁶	8000 (16000 @60sec)	10000 (18000 @60sec)	12000 (18000 @60sec)	15000 (18000 @60sec)	
Max. Output Apparent Power with Grid (VA)	6000	8000	10000	12000	15000	
Max. Output Current (A)	13.0 (17.4 @60sec)	17.4 (23.3 @60sec)	21.7 (26.1 @60sec)	21.7 (26.1 @60sec)	21.7 (26.1 @60sec)	
Nominal Output Voltage (V)				400 / 380		
Nominal Output Frequency (Hz)				50 / 60		
Output THDv (@Linear Load)				<3%		
Efficiency						
Max. Efficiency	98.0%	98.0%	98.2%	98.2%	98.2%	
European Efficiency	97.2%	97.2%	97.5%	97.5%	97.5%	
Max. Battery to AC Efficiency	97.2%	97.5%	97.5%	97.5%	97.5%	
MPPT Efficiency				99.5%		
Protection						
PV Insulation Resistance Detection				Integrated		
PV AFCI3.0				Optional		
Residual Current Monitoring				Integrated		
PV Reverse Polarity Protection				Integrated		
Battery Reverse Polarity Protection				Integrated		
Anti-islanding Protection				Integrated		
AC Overcurrent Protection				Integrated		
AC Short Circuit Protection				Integrated		
AC Overvoltage Protection				Integrated		
DC Switch				Integrated		
DC Surge Protection				Type II		
AC Surge Protection				Type II		
Remote Shutdown				Integrated		
General Data						
Operating Temperature Range (°C)				-35 ~ +60		
Relative Humidity				0 ~ 100%		
Max. Operating Altitude (m)				4000		
Cooling Method				Natural Convection		
User Interface				LED, WLAN + APP		
Communication with BMS				RS485, CAN		
Communication with Meter				RS485		
Communication with Portal				WiFi + LAN + Bluetooth		
Weight (kg)	23	23	25	25	25	
Dimension (W x H x D mm)				496 x 460 x 221		
Noise Emission (dB)	<30	<30	<30	<45	<45	
Topology				Non-isolated		
Self-consumption at Night (W) ⁷				<15		
Ingress Protection Rating				IP66		
Mounting Method				Wall Mounted		

*1: Max. Input Power, not continuous for 1.6*normal power. Besides, in Australia, for most of the PV module, the max. input power can achieve 2*Pn, Such as the max. input power of GW6000-ET-20 can achieve 12000W.

*2: For 1000V system, Maximum operating voltage is 950V.

*3: According to the local grid regulation.

*4: Output Voltage Range: phase voltage.

*5: The Max. AC Current Output to on-grid load is 13A, 17.4A, 21.7A, 21.7A, 21.7A, 21.7A separately.

*6: Can be reached only if PV and battery power is enough.

*7: No Back-up Output.

*: Please visit GoodWe website for the latest certificates.